

V550C2

Engine VOLVO , TAD1641GE
Alternator LEROY SOMER , LSA472M7

STANDARD FEATURES

- Electronic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for wiring temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 24 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
415/240	440 / 550	400 / 500	765		
400/230	440 / 550	400 / 500	794	Leng : 3470mm [137in]	3620kg [7981lbs] Net
380/220	440 / 550	400 / 500	836	Widt : 1500mm [59in]	4160kg [9171lbs] Gross
240 TRI	440 / 550	400 / 500	1323	Heig : 2043mm [80in]	
230 TRI	440 / 550	400 / 500	1381		
220 TRI	440 / 550	400 / 500	1443		
200/115	440 / 550	400 / 500	1588		



POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1.

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions ESP/PRP 27 C°/40 C° Air Intlet Temp, 1000 m/1000 m m A.S.L. 60 % relative humidity.

	Model	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
	M229-DW	78.1	68	Leng : 5083mm [200in] Widt : 1560mm [61in] Heig : 2700mm [106in]	5590kg [12324lbs] 7240kg [15961lbs]	1770 L
	M229	78.1	68	Leng : 5031mm [198in] Widt : 1560mm [61in] Heig : 2435mm [96in]	4870kg [10737lbs] 5410kg [11927lbs]	500 L



ENGINE SPECIFICATIONS

DATA GENERAL DATA	Motor model	VOLVO TAD1641GE , 4-temps, TURBO , AIR/AIR 6 X
	Cylinder arrangement	L
	Displacement (C.I.)	16.12
	Bore (mm) X Stroke (mm)	144 X 165
	Compression ratio	16.5 : 1
	Speed (RPM)	1500
	Pistons speed (m/s)	8.25
	Maximum stand-by power at rated RPM (kW)	473
	Frequency regulation (%)	0.5
	BMEP (bar)	21.34
	Governor type	ELEC
EXHAUST SYSTEM	Exhaust gas temperature (°F)	455
	Exhaust gas flow (L/s)	1533
	Max. exhaust back pressure (mm CE)	1000
FUEL SYSTEM	Consumption @ 110% load (L/h)	112.56
	Consumption @ 100% load (L/h)	102.05
	Consumption @ 75% load (L/h)	75.38
	Consumption @ 50% load (L/h)	51.02
	Maximum fuel pump flow (L/hr)	170
OIL	Oil capacity (L)	48
	Min. oil pressure (bar)	0.7
	Max. oil pressure (bar)	6.5
	Oil consumption 100% load (L/h)	0.1
	Carter oil capacity (L)	42
THERMAL BALANCE	Heat rejection to exhaust (kW)	326
	Radiated heat to ambient (kW)	20
	Heat rejection to coolant (kW)	184
AIR INTAKE	AIR INTAKE_entree_max%	500
	Intake air flow (L/s)	633
COOLANT SYSTEM	Radiator & Engine capacity (L)	60
	Max water temperature (°C)	103
	Outlet water temperature (°C)	93
	Fan power (kW)	11
	Fan air flow w/o restriction (m3/s)	10.9
	Available restriction on air flow (mm CE)	30
	Type of coolant	GLYCOL
	Thermostat (°C)	86-96
EMISSIONS	Emissions PM (g/kW.h)	0.086
	Emission CO (g/kW.h)	1.15
	Emissions HCNOx (g/kWh)	N/A
	Emission HC (g/kW.h)	0.12

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products.



ALTERNATOR SPECIFICATIONS

DATA GENERAL DATA	Alternator brand	LEROY SOMER
	Alternator	LSA472M7
	Number of phase	3
	Power factor (Cos Phi)	0.8
	Altitude (m)	<1000
	Overspeed (rpm)	2250
	Number of pole	4
	Excitation system	SHUNT
	Insulation class / Temperature class	H / H
	Regulation	R230
	Total harmonics TGH/THC	<2
	Wave form : NEMA=TIF-TGH/THC	<50
	Wave form : CEI=FHT-TGH/THC	<2
	Number of bearing	1
	Coupling	DIRECT
	Voltage regulation 0 à 100%	0.5
	Recovery time (Delta U = 20% transitoire) (ms)	500
OTHER	Continuous Nominal Rating 40°C (kVA)	500
	Standby Rating 27°C (kVA)	570
	Efficiencies 4/4 load (%)	94.5
	Air flow (m3/s)	0.9
	Short circuit ratio (Kcc)	0.41
	Direct axis synchro reactance unsaturated (Xd) (%)	307
	Quadra axis synchro reactance unsaturated (Xq) (%)	184
	Open circuit time constant (T'do) (ms)	1930
	Direct axis transient reactance saturated (X'd) (%)	15.9
	Short circuit transient time constant (T'd) (ms)	100
	Direct axis subtransient reactance saturated (X''d) (%)	12.7
	Subtransient time constant (T''d) (ms)	10
	Quadra axis subtransient reactance saturated (X''q) (%)	16.8
	Zero sequence reactance unsaturated (Xo) (%)	0.7
	Negative sequence reactance saturated (X2) (%)	14.8
	Armature time constant (Ta) (ms)	15
	No load excitation current (io) (ms)	1
Full load excitation current (ic) (A)	3.6	
Full load excitation voltage (uc) (A)	36	
Recovery time (Delta U = 20% transitoire) (ms)	500	
Motor start (Delta U = 20% perm. or 50% trans.) (ms)	1073	
Transient dip (4/4 charge) - PF : 0,8 AR (%)	14.6	
No load losses (kW)	6.54	
Heat rejection (kW)	23.04	

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products.

SDMO Generators

Tel: +44(0)8458 388 562 – www.sdmo-generators.com



CONTROL PANEL

Standard



TELYS


TELYS

Specifications : Frequency meter, Ammeter, Voltmeter

Alarms and faults : Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop

Engine parameters : Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level

Option



KERYS

KERYS

Specifications : Frequency meter, Ammeter, Voltmeter

Alarms and faults : Oil pressure, water temperature, No start-up, Overspeed, Min/max alternator, Min/max battery voltage, Low fuel level, Emergency stop

Engine parameters : Hours counter, Oil pressure, Water temperature, Engine speed, Battery voltage, Fuel level

Additional specifications : Website, Troubleshooting, Assistance and Maintenance, Plotting and logging, Load impact, 8 configurations available, Compliance with international standards...